GROUND MOVING

- Extremely tough and rugged
- Angle up to 30 degrees
- Heavy cylinders
- Replaceable bolt-on edge
- Skid loader attachments





DOZER BLADE













Hydraulic hoses with quick couplings

Shockproof valve

DOZER TILT BLADE















Hydraulic hoses with quick couplings

Shockproof valve

1/2" valve

Hydraulic oscillation +/- 8°

Standard electric kit

LEVELING BOX DOZER BLADE





Proportional distributor


Rear pad with hydraulic control which neutralizes the riding effect

Laser control system

Bolt-in blade

Electrically controlled kit





DIMENSIONS

				DB 210		
А	Width	1510	1810	2110	2410	2710
В	Depth	600	600	600	600	600
С	Height	730	730	730	730	730

- It is equipped with shockproof valve
- HB400 wear&tear steel bolted blade



The M3 dozer blade can be easily fitted to any kind of skid steer loader.

It is equipped with shockproof valve, hydraulic angling \pm 30°, electric valve with hydraulic hoses, HB400 wear&tear steel bolted blade and universal attachment to fit the machine.











MODEL	DB 150	DB 180	DB 210	DB 240	DB 270
Working width [mm]	1299	1560	1820	2075	2330
Weight [kg]	340	370	400	420	450
Hydraulic blade inclination r/l	±30°	±30°	±30°	±30°	±30°



