GROUND MOVING

- Extremely tough and rugged
- Angle up to 30 degrees
- Heavy cylinders
- Replaceable bolt-on edge
- Skid loader attachments





DOZER BLADE



Hydraulic hoses with quick couplings

Shockproof valve

DOZER TILT BLADE













Hydraulic hoses with quick couplings

Shockproof valve

1/2" valve

Hydraulic oscillation +/- 8°

Standard electric kit

LEVELING BOX DOZER BLADE





Proportional distributor


Rear pad with hydraulic control which neutralizes the riding effect

Laser control system

Bolt-in blade

Electrically controlled kit





		TDB 180	TDB 210	TDB 240	TDB 270
4	Width	1810	2110	2410	2710
3	Depth	600	600	600	600
2	Height	730	730	730	730

- It is equipped with shockproof valve
- HB400 wear&tear steel bolted blade
- Electric valve complete with hydraulic hoses



The M3 tilt dozer blade can be easily fitted to any kind of skid steer loader.

It is equipped with shockproof valve, hydraulic angling \pm 30°, hydraulic oscillation \pm 8°, electric valve with hydraulic hoses, HB400 wear&tear steel bolted blade and attachment to fit skid loader.













MODEL	TDB 180	TDB 210	TDB 240	TDB 270			
Working width [mm]	1560	1820	2075	2330			
Weight [kg]	360	390	430	490			
Max pressure [bar]	250	250	250	250			
Oil flow [l/min]	100	100	100	100			
Hydraulic blade inclination r/l	±30°	±30°	±30°	±30°			
Hydraulic blade oscillation r/l	±8°	±8°	±8°	±8°			

