



DIMENSIONS

	MHC5 160	MHC5 180	MHC5 200	MHC10 160 HD	MHC10 180 HD
Width	182	202	222	200	220
Depth	120	120	120	100	100
Height	110	110	110	160	160

- Maximum cutting diameter: 8 cm 30 cm (HD series only)
- Hydraulic motor with belt transmission
- MKF knives rotor
- MHF hammers rotor

The M3 MHC series bushcutter featured by its solidity, is designed to fit skid loaders, compact and telescopic loaders up to 80/90 HP. Available in 2 versions, standard and HD. **The standard version** is equipped with universal oscillating and self-leveling attachment, mechanical side movement, valve block, sturdy and reinforced structure, helical rotor with tempered hammers (standard) or knives (optional), hydraulic motor with V-belt transmission. **The HD version** in addition is equipped with universal fixed attachment, rotor with fixed widia teeth, reinforced wear-resistant structure, pressure gauge for working pressure control, double rear chains for greater protection, piston motor and high performance HTD single belt transmission.

OPTIONALS	Hydraulic shift (not available in the HD series)	Hydraulic hoses kit
Hydraulic kit for front hood drive	Attachment for Backhoes / loaders / telehandlers	Mechanical push frame (only available in the HD series)











I >	3
	=
⋝	5
۵	4
	П
Ξ	=
H	8
-	•
	7
_	,
2	3
U	3
=	2
V	٦
١	-
L	د
	1
_	4
=	3
2	r
n	7
2	₹
	2
>	-
	-

MODEL	MHC5 160	MHC5 180	MHC5 200	MHC10 160 HD	MHC10 180 HD	
Working width [mm]	1600	1800	2000	1600	1800	
Weight [kg]	890	930	970	1285	1420	
Oil [lt/min]	60/120	60/120	60/120	100/180	100/180	
Pression [bar]	200/220	200/220	200/220	200/350	200/350	
Skid loader class [hp]	50/90	50/90	50/90	70/120	70/120	
Rotor standard	MHF16	MHF16	MHF16	MHF14	MHF14	
Rotor optional	MKF3	MKF3	MKF3	MHF15	MHF15	
Motor displacement [cc]	27/51	27/51	27/51	45/80	45/80	
Motor type	cast iron gears			pistons gears		
Knives number [n°]	18	20	22	42	54	

